

What is claimed is:

1. A method of protecting a circuit having power switching devices, the method comprising:

defining characteristics of a zone of protection of the circuit;

defining a protection matrix based at least in part upon said characteristics;

and

performing a zone protective function on said zone of protection using said protection matrix.

2. The method of claim 1, wherein said zone protective function is a plurality of zone protective functions, each of said plurality of zone protective functions being performed on said zone of protection based at least in part upon said protection matrix.

3. The method of claim 1, wherein the step of performing said zone protective function is based at least in part upon electrical parameters of said zone of protection, said electrical parameters being communicated over a network to a microprocessor.

4. The method of claim 3, further comprising sensing said electrical parameters with a sensor, communicating signals representative of said electrical parameters to a module, and communicating said signals to said microprocessor, wherein said module, said sensor and said microprocessor are communicatively coupled over said network.

5. The method of claim 1, further comprising:

monitoring a topology of the circuit, said topology being based at least in part upon a status for each of the power switching devices in the circuit, said status being either opened or closed;

defining said zone of protection based at least in part upon said topology; and

adjusting said zone of protection based at least in part upon changes to said topology.

6. The method of claim 1, wherein the step of defining said characteristics comprises defining a plurality of combinations of states of the power switching devices in said zone of protection, each of said states being either opened or closed.

7. The method of claim 6, wherein the step of defining said characteristics further comprises defining power flow configurations for said zone of protection based upon said plurality of combinations of said states of the power switching devices in said zone of protection.

8. The method of claim 7, further comprising:

defining a definition matrix based at least in part upon said power flow configurations; and

defining said protection matrix based at least in part upon said definition matrix.

9. The method of claim 6, further comprising:

defining a zone state matrix based upon said plurality of combinations of said states of the power switching devices in said zone of protection; and

defining said protection matrix based at least in part upon said zone state matrix.

10. The method of claim 6, further comprising opening at least one of the power switching devices in said zone of protection based upon said zone protective function.

11. The method of claim 10, wherein a microprocessor is configured to operate each of the power switching devices in the circuit.

138362

12. The method of claim 11, further comprising:

determining a dynamic delay time for opening said at least one of the power switching devices; and

opening said at least one of the power switching devices after said dynamic delay time has elapsed.

13. A method of protecting a circuit having power switching devices, the method comprising:

defining a plurality of combinations of states of the power switching devices disposed in a zone of protection of the circuit, each of said states being either opened or closed;

defining characteristics of said zone of protection based at least in part upon said plurality of combinations of said states of the power switching devices disposed in said zone of protection, said characteristics being actual and possible characteristics; and

performing a zone protective function on said zone of protection based at least in part upon said characteristics.

14. The method of claim 13, wherein said zone of protection is dynamic.

15. The method of claim 13, wherein the step of defining said characteristics comprises defining power flow configurations for said zone of protection based upon said plurality of combinations of said states of the power switching devices disposed in said zone of protection.

16. The method of claim 13, wherein said zone protective function is a plurality of zone protective functions, each of said plurality of zone protective functions being performed on said zone of protection based at least in part upon said characteristics of said zone of protection.

17. The method of claim 13, wherein the step of performing said zone protective function is based at least in part upon electrical parameters of said zone of protection, said electrical parameters being communicated over a network to a microprocessor.

18. The method of claim 17, further comprising sensing said electrical parameters with a sensor, communicating signals representative of said electrical parameters to a module, and communicating said signals to said microprocessor, wherein said module, said sensor and said microprocessor are communicatively coupled over said network.

19. The method of claim 13, further comprising:

monitoring a topology of the circuit, said topology being based at least in part upon a status for each of the power switching devices in said circuit, said status being either opened or closed;

defining said zone of protection based at least in part upon said topology; and

adjusting said zone of protection based at least in part upon changes to said topology.

20. The method of claim 13, further comprising opening at least one of the power switching devices in said zone of protection based at least in part upon said zone protective function.

21. The method of claim 20, wherein a microprocessor is configured to operate each of the power switching devices in said circuit.

22. The method of claim 20, further comprising:

determining a dynamic delay time for opening said at least one of the power switching devices; and

opening said at least one of the power switching devices after said dynamic delay time has elapsed.

23. A method of protecting a circuit having power switching devices, the method comprising:

defining a plurality of configurations for a zone of protection of the circuit, said plurality of configurations being actual and possible configurations, said plurality of configurations being based at least in part upon states of the power switching devices disposed in said zone of protection, each of said states being either opened or closed;

defining a plurality of coefficients for a zone protective function based at least in part upon said plurality of configurations;

determining a first topology for said zone of protection, said first topology being based upon a first status for each of the power switching devices disposed in said zone of protection, said first status being either opened or closed;

selecting at least one of said plurality of coefficients based upon said first topology; and

performing said zone protective function on said zone of protection based at least in part upon said at least one of said plurality of coefficients that has been selected.

24. The method of claim 23, wherein the step of defining said plurality of coefficients comprises defining power flow paths for said zone of protection based upon said plurality of configurations.

25. The method of claim 23, wherein said zone protective function is a plurality of zone protective functions, each of said plurality of zone protective functions being performed on said zone of protection based at least in part upon said plurality of coefficients.

26. The method of claim 23, wherein the step of performing said zone protective function is based at least in part upon electrical parameters of said zone of protection, said electrical parameters being communicated over a network to a microprocessor.

27. The method of claim 26, further comprising sensing said electrical parameters with a sensor, communicating signals representative of said electrical parameters to a module, and communicating said signals to said microprocessor, wherein said module, said sensor and said microprocessor are communicatively coupled over said network.

28. The method of claim 23, further comprising the steps of:

monitoring a second topology of the circuit, said second topology being based at least in part upon a second status for each of the power switching devices in said circuit, said second status being either opened or closed;

defining said zone of protection based at least in part upon said second topology; and

adjusting said zone of protection based at least in part upon changes to second said topology.

29. The method of claim 23, further comprising opening at least one of the power switching devices in said zone of protection based at least in part upon said zone protective function.

30. The method of claim 29, wherein a microprocessor is configured to operate each of the power switching devices in said circuit.

31. The method of claim 29, further comprising:

determining a dynamic delay time for opening said at least one of the power switching devices; and

opening said at least one of the power switching devices after said dynamic delay time has elapsed.

32. A protection system for coupling to a circuit having power switching devices and a zone of protection, the system comprising:

a control processing unit being communicatively coupleable to the power switching devices so that said control processing unit can perform a zone protective function on said zone of protection based at least in part upon characteristics of said zone of protection, said characteristics being actual and possible characteristics.

33. The system of claim 32, wherein said characteristics are defined at least in part by a plurality of configurations for said zone of protection, said plurality of configurations being based at least in part upon states of the power switching devices disposed in said zone of protection, each of said states being either opened or closed.

34. The system of claim 33, wherein said characteristics are based at least in part upon power flow paths for said zone of protection, said power flow paths being based upon said states of said power switching devices disposed in said zone of protection.

35. The system of claim 32, wherein said control processing unit defines said zone of protection.

36. The system of claim 35, wherein said zone of protection is dynamic.

37. The system of claim 32, wherein said control processing unit monitors a topology of the circuit, said topology being based at least in part upon a status for each of the power switching devices in the circuit, said status being either opened or closed, wherein said control processing unit defines said zone of protection based at least in part upon said topology, and wherein said control processing unit adjusts said zone of protection based at least in part upon changes to said topology.

38. The system of claim 32, wherein said zone protective function is a plurality of zone protective functions, each of said plurality of zone protective functions being performed on said zone of protection based at least in part upon said characteristics of said zone of protection.

39. The system of claim 32, further comprising a network in communication with said control processing unit and communicatively coupleable to the power switching devices.

40. The system of claim 39, wherein said control processing unit operatively controls the power switching devices.

41. The system of claim 39, wherein said control processing unit receives parameter signals representative of electrical parameters of the circuit, and wherein said control processing unit opens the power switching devices if a fault is detected in the circuit.

42. The system of claim 41, further comprising a module and a sensor, said module being in communication with the power switching devices, said sensor and said control processing unit, wherein said sensor senses said electrical parameters and communicates said parameter signals to said module, and wherein said module communicates said parameter signals to said control processing unit.

43. The system of claim 32, wherein said control processing unit opens at least one of the power switching devices in said zone of protection based at least in part upon said zone protective function.

44. The system of claim 32, wherein said control processing unit determines a dynamic delay time for opening at least one of the power switching devices, and wherein said at least one of the power switching devices is opened after said dynamic delay time has elapsed.

45. The system of claim 32, wherein said control processing unit utilizes a protection matrix to perform said zone protective function, said protection matrix being defined at least in part by said characteristics of said zone of protection.
46. A power distribution system comprising:
- a circuit having power switching devices and a zone of protection; and
 - a control processing unit communicatively coupled to said power switching devices, wherein said control processing unit performs a zone protective function on said zone of protection based at least in part upon characteristics of said zone of protection, said characteristics being actual and possible characteristics.
47. The system of claim 46, wherein said characteristics are defined at least in part by a plurality of configurations for said zone of protection, said plurality of configurations being based at least in part upon states of said power switching devices disposed in said zone of protection, each of said states being either opened or closed.
48. The system of claim 46, wherein said characteristics are based at least in part upon power flow paths for said zone of protection, said power flow paths being based upon said states of said power switching devices disposed in said zone of protection.
49. The system of claim 46, wherein said control processing unit defines said zone of protection.
50. The system of claim 49, wherein said zone of protection is dynamic.
51. The system of claim 46, wherein said control processing unit monitors a topology of said circuit, said topology being based at least in part upon a status for each of said power switching devices in said circuit, said status being either opened or closed, wherein said control processing unit defines said zone of protection based at least in part upon said topology, and wherein said control processing unit adjusts said zone of protection based at least in part upon changes to said topology.

158302

52. The system of claim 46, wherein said zone protective function is a plurality of zone protective functions, each of said plurality of zone protective functions being performed on said zone of protection based at least in part upon said characteristics of said zone of protection.

53. The system of claim 46, wherein said control processing unit operatively controls said power switching devices.

54. The system of claim 46, further comprising a network in communication with said control processing unit and said power switching devices.

55. The system of claim 54, wherein said control processing unit receives parameter signals representative of electrical parameters of said circuit, and wherein said control processing unit opens said power switching devices if a fault is detected in said circuit.

56. The system of claim 55, further comprising a data sample and transmission module and a sensor, said module being in communication with said power switching devices, said sensor and said control processing unit, wherein said sensor senses said electrical parameters and communicates said parameter signals to said module, and wherein said module communicates said parameter signals to said control processing unit.

57. The system of claim 46, wherein said control processing unit opens at least one of said power switching devices based upon said zone protective function.

58. The system of claim 46, wherein said control processing unit determines a dynamic delay time for opening at least one of said power switching devices, and wherein said at least one of said power switching devices is opened after said dynamic delay time has elapsed.

150502

59. The system of claim 46, wherein said control processing unit utilizes a protection matrix to perform said zone protective function, said protection matrix being defined at least in part by said characteristics of said zone of protection.